



DK SERIES

DK861DR4


86" 3500 nits UHD Dual-Sided Ultra-High Brightness Outdoor Kiosk




DUAL-SIDED
DESIGN



SUNLIGHT
VIEWABLE IMAGE



VANDAL
RESISTANT



VIEWABLE WITH
POLARIZED LENSES



WEATHER
PROOF

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

SPECIFICATION

MODEL	DK861DR4
DISPLAY	<p>LCD Panel Size 85.6" inches LCD (x2)</p> <p>Native Resolution 3840 x 2160</p> <p>Backlight LED</p> <p>Brightness 3,500 nits</p> <p>Light Lifetime (Typ.) 100,000 hrs</p> <p>Contrast Ratio 3000 : 1</p> <p>Color Depth 10 bits</p> <p>Viewing Angle 178° / 178°</p> <p>Blackening Defect Free Up to 110°C (230°F)</p> <p>Polarized Sunglasses Support Yes</p> <p>Touch Function (Optional) P-Cap touch</p>
POWER	<p>Power Supply Internal</p> <p>Rated Voltage 200-240V ~ 50/60HZ</p> <p>Power On Mode (Typ./ Max) 1300W / 3000W</p>
MECHANICAL SPECS	<p>Bezel Width (T/B/L/R) 95.2 / 106.7 / 134.4 / 134.4 mm</p> <p>Cabinet Color Black</p> <p>Dimension (LxHxD, w/o stand) 1338.0 x 2174.0 x 254.0 mm</p> <p>Weight 500 kg</p> <p>Orientation Portrait</p> <p>Reserved Space for Optional Player Yes</p> <p>High Security Lock Yes</p>
USER INTERFACE	<p>Language English</p> <p>Support SNMP (Up to V3.0) Yes</p> <p>Local Dimming Control Yes</p> <p>Ambient Light Sensor Yes</p> <p>Power On/Off Scheduling Yes</p> <p>Internal Temperature Sensor Yes</p> <p>Backup Player Build-in Yes</p>
INPUT	<p>HDMI x6 (2160p)</p> <p>Display Port x2</p> <p>USB 3.0 x2</p> <p>Micro SD Slot x2</p>
OUTPUT	Audio x2
EXTERNAL CONTROL	<p>RS-232 In x2</p> <p>RJ-45 x4 (LAN)</p>
ENVIRONMENT	<p>Operating Temperature -30° C ~ 50° C</p> <p>Storage Temperature -20° C ~ 60° C</p> <p>Humidity 10% ~ 100% RH Non-condensing</p> <p>Environmental Rating IP56 / IK10 / ASTM G155</p>
CERTIFICATION	CE / FCC / UL / ROHS

DIMENSIONS

