InstaShow® VS20

Wireless Video Conferencing System

Smooth Collaboration in Hybrid Meetings

VS20 is the ultimate wireless presentation and video conferencing device with 4K video output, embedded microphone, and intuitive features such as touchback and extended screen, perfect for high-quality and collaborative hybrid meetings.

Hassle-free IT Management

Ease the burden of IT management with VS20, featuring a user-friendly web interface and secure data management through WPA2 encryption, leaving you free from any IT headaches.



The BenQ VS20 system offers seamless **plug-and-play screen sharing** during meetings, with the option to install advanced BenQ software and make use of features that facilitate hybrid video conferences.



The VS20 video conferencing solution boasts a unique **built-in microphone** button and the ability to configure an **external camera** for flexible video source options.



The **switchable dual interface** allows for easy switching between USB Type-C or Type-A cables for the button.



Versatile and flexible, the VS20 is ideal for meetings of any size, from small huddle rooms to large boardrooms, thanks to its extensive **20-metre transmission distance**.



VS20 fully supports **BYOM** with Windows devices, allowing users to bring their own device and preferred conferencing solution to host a video conference.



TECHNICAL SPECIFICATIONS

General	
Model Name	VS20
Interface	USB Type-C (With one spare cable: USB Type-A and HDMI)
Input Resolution	Up to 4k @30fps
Output Resolution	Up to 4k @60fps
Split Mode	4 split mode (on/off)
Simultaneous Connections	32 pcs
Wi-Fi Standard	IEEE 802.11ac, 5GHz, 2T2R, IEEE 802.11n, 2.4GHz 5GHz , 2T2R
Maximum Data Rate	Up to 867 Mbps
Frequency Band	2.4GHz, 5GHz
Wi-Fi Authentication	WPA2 AES 128bit / WPA2 enterprise 256bit
WAN	1 Gbps
Supported Platform (BYOM)	Windows
Supported Mobile Display	Airplay, MiraCast
Environmental	
Reach Distance	Max. 20m
Power Consumption	Receiver: 11W/36W (Typical/Max)
Standby Power Consumption	<0.5W
Weight (Net)	530g (Receiver x1 + Button x2)
Operating Temperature	0°C to 40°C
Others	
Vulnerability Test	No vulnerability risk
OSD Language	Czech/Danish/German/English/European Spanish/Finnish/European French/Italian/Japanese/Korean/Norwegian/Polish/Brazilian Portuguese/Russian/Swedish/Simplified Chinese/Traditional Chinese
Accessory	Receiver x1, Button x2, Cradle x1, Antenna x4, Power adapter x1, Quick start guide x1, Spare cable x1 (USB Type-A and HDMI)
Part Number	9H.JRS78.NIE
EAN Code	471 8755 08888 9







