

UHZ65UST

Ultra short throw smart laser 4K Ultra HD projector









- Ultra short throw laser projector 4K UHD resolution, HDR and HLG compatible
- Amazing colour 87% DCI-P3, 3500 ANSI lumens
- Built-in NuForce soundbar with DolbyDigital 2.0
- Smart features Apps, voice control, IFTTT

This stylish ultra short throw projector delivers an unforgettable 4K UHD digital cinema quality image in the comfort of your own home. Laser technology provides accurate, true to life colour reproduction with 87% of DCI-P3 coverage - perfect for recreating the big-screen experience at home.

Packed with the latest technology and features, the UHZ65UST boasts HDR and HLG compatibility, sophisticated PureMotion frame-interpolation processing which eliminates motion blurring or image judder, voice control, streaming apps and a built-in media player.

Specifications

Power consumption (min)

Power consumption (max)

Dimensions (W x D x H)

Net weight

Weight and dimensions

Display/image Display technology DLP Resolution UHD (3840x2160) Brightness 3,500 lumens 2,500,000:1 Contrast ratio 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Horizontal scan rate 31 ~ 135Khz Vertical scan rate 24 ~ 120Hz 90% Uniformity 2.16m ~ 3.05m (85" ~ 120") diagonal Screen size Lamp info Light source type LASER life 20,000 hours Optical 0.25:1 Throw ratio Projection distance (m) 0.47m - 0.66m Focal length (mm) 525 Vertical +0% Lens shift Native offset 124% Connectivity Connections Inputs 3 x HDMI 2.0, 1 x USB-A reader Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x USB-A service, 1 x RJ45 General Noise level (typical) PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 3D compatibility Frame-pack: 1080p24, 720p50 / 60 Security Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese OSD / display languages Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Yes 2 Speaker count Watts per speaker 10W In the box AC power cord Rechargeable remote control Basic user manual Networking LAN - control Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption 0.5W (standby)

220W

345W

11kg

576 x 383 x 130

