

# BLANKORA P

## TECHNICKÝ POPIS

Základní materiál :	termoplast vyztužený tkaninou
Projekční strana :	matně bílá
Zadní strana :	bílá
Tloušťka :	0,45 mm
Hmotnost :	530 g/m <sup>2</sup>
Šíře role :	300 cm
Svařitelný :	ano
Omyvatelný :	ano
Hořlavost :	B1 dle DIN 4102 část 1
Reflexní skupina :	D (difuzní)
Použití :	přední projekce
Neprůsvitnost :	>100%
Gain :	1,0
Pozorovací úhel :	+/- 60°
Vhodné pro rozlišení :	2K

## VLASTNOSTI

- široký pozorovací úhel, projekční světlo se odráží do všech směrů
- přirozené podání barev
- světlo nepropustná černá zadní strana (>100%)
- možnost černého rámečku
- čištění vodou

## POUŽITÍ

Rollovací promítací plátna do šíře 300 cm

## PERFORMANCE

Base material :	woven fiberglass
Projection side :	matt white
Rear side :	white
Thickness :	0,45 mm
Weight :	530 g/m <sup>2</sup>
Roll width :	300 cm
Weldable :	yes
Washable :	yes
Fire resistance :	B1 acc. DIN 4102 part 1
Screen type :	D (diffuse)
Application :	front projection
Light proof :	>100%
Gain :	1,0
Viewing angle :	+/- 60°
High resolution compatibility :	2K

## CHARACTERISTICS

- wide viewing angle, projected light is diffused in all directions
- accurate and natural color rendition
- lightproof back layer (>100%)
- black masking available
- clean with water

## APPLICATION

Roll up projection screens up to width 300 cm

FAKTOR JASU MĚŘEN DLE DIN 19045 | GAIN ACCORDING TO DIN 19045

